

RL5000

*RL5000 with
high-topper*

It's simply the most cost-competitive embedded PC ATM in the market.

Triton's embedded PC-based RL5000 has changed the way people think about ATMs. This model offers a long list of value-added transactions with couponing, decals, signage, and also customized display ads on a stunning 10.4 inch LCD display — all at a much lower price point than other PC-based machines.

This model's popularity is due, in part, to the innovation made possible by Intel XScale®, a new level of high-performance and hassle-free operation. It's also becoming one of Triton's top selling models because of its capability to store a large capacity of journal records and the ease of downloading graphics for enhanced marketing efforts.

In addition to its low price, the RL5000 offers an extremely low cost of operation. The wide range of dispensers available offers customers

the ability to choose the capacity that most matches their usage, and — like all Triton technology — it's extremely easy to service. Plus, the RL5000 has all the standards you are looking for in a new ATM: TCP/IP communication, ADA compliant, Visa Encrypting PIN Pad (VEPP), and Triple DES compliance.

There's not another embedded PC ATM on the market that offers the level of performance and cost-competitiveness delivered by the Triton RL5000. The future of ATMs is here.

 **Triton**
WHERE MONEY COMES FROM.®
A DOVER COMPANY



RL5000
with mid-topper

RL5000

In Detail

The future of ATMs is here.

FEATURES:

- 10.4" (264 mm) VGA color display with 640 x 480 resolution
- One to four cassettes
- 80 mm thermal printer with presenter
- 2 MB journal storage (32,768 records)
- Triton Connect™ compatible
- Dip-style card reader; optional dip EMV smart card reader, EMV motorized card reader (Track 1,2,3)
- Americans with Disabilities Act (ADA) and audio compliant
- Visa Encrypting PIN Pad (VEPP) to comply with all international encryption standards
- UL 291 Business Hours cabinet or optional UL 291 Level 1 Safe
- Electronic lock or optional Kaba Mas Cencon lock
- Multi-lingual capabilities
- Dial-up 56k baud internationally certified modem and TCP/IP communications
- Dimensions:
 - Width: 16.9" (429 mm)
 - Depth: 25.6" (650 mm)
 - Height: 54.3" (1390 mm) without topper
 - Height: 64.9" (1648 mm) with mid-topper
 - Height: 77.8" (1976 mm) with high-topper
- Weight up to 640 lb (290 kg)
- Advertising revenue potential:
 - Decals and signage
 - Couponing
 - Display graphics

OPERATING SYSTEM:

- Intel XScale®
- Microsoft® Windows® CE .NET
- 32 MB flash memory, expandable
- 64 MB RAM, expandable
- Four USB master ports
- Two PCMCIA card slots
- Five serial ports


OPERATING SPECS:

- Temperature:
 - 10° to 40° C / 50° to 104° F
- Relative humidity:
 - 20% to 80% non-condensing
- Power consumption:
 - 2.0 A @ 115 VAC at 60 Hz
 - 1.0 A @ 230 VAC at 50 Hz

Triton Headquarters • 522 East Railroad Street
Long Beach, Mississippi 39560 USA
With offices throughout the U.S. and worldwide
including Canada, UK, Australia, and Hong Kong
Phone: 1-228-868-1317 • Toll free: USA & Canada 1-800-367-7191
www.triton.com • Email: sales@triton.com

© 2007 Delaware Capital Formation, Inc. All Rights Reserved. TRITON, TRITON WHERE MONEY COMES FROM, DOVER and DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.

Current as of 02/07 · RL5000 product sheet-07203-00034



*The dimensions shown comply with U.S. Federal ADA guidelines. For installation within the U.S., be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed. *specifications subject to change without notice*

ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE